

The **nccstretch** package^{*}

Alexander I. Rozhenko
rozhenko@oapmg.ssc.ru

2004/11/30

1 User Interface

\stretchwith The package implements the command

```
\stretchwith{\langle foo \rangle}{\langle text \rangle}
```

that stretches the *<text>* parameter inserting the *<foo>* sequence between every pair of neighbour tokens of the *<text>*. Spaces in the text are ignored. So, to save a space, you need to insert a backslash before it or enclose a space in braces. If you do not want to insert *<foo>* between some tokens, enclose them in braces. While stretching, all first-level braces are removed. The examples below show some use cases (we delimit the results with rules to show exactly how the command works):

Command	Result
<code>\stretchwith{\,}{Proof\ of\ Theorem\ 1}</code>	<code>\ Proof of Theorem 1 </code>
<code>\stretchwith{.}{\ test{ }test{}}\ \ {test}{\"e}}</code>	<code> .t.e.s.t. .t.e.s.t... .t.e.s.t </code>
<code>\makebox[1.5\width]{\stretchwith{\hfill}{test\ test}}</code>	<code>test test </code>

2 The Implementation

\stretchwith The command is implemented using `\@tfor` cycle. The `\@tempa` command contains a sequence to be inserted before the next token. It is set to `\relax` before the cycle and is set to *<foo>* after every inserted token. This trick allows insert *<foo>* **between** neighbour tokens only.

```
1 <*package>
2 \newcommand*\stretchwith[2]{%
3   \let\@tempa\relax
4   \def\@tempb{\#1}%
5   \@tfor\@tempc:=#2\do {\@tempa \@tempc \let\@tempa\@tempb}%
6 }
7 </package>
```

^{*}This file has version number v1.0, last revised 2004/11/30.