

The **ncccropmark** package*

Alexander I. Rozhenko
rozhenko@oapmg.sscc.ru

2004/11/29

1 User Interface

cropmark The package implements the command

```
\cropmark[\langle fields \rangle]{\langle left \rangle}{\langle right \rangle}{\langle top \rangle}{\langle bottom \rangle}{\langle length \rangle}
```

useful as a watermark. The command was desired for use together with the **watermark** package. It must be called inside the picture environment (a watermark content is prepared in such a way).

The optional *<fields>* parameter contains a combination of letters **h** (header), **f** (footer), and **m** (marginal notes). It determines the additional fields of paper area to be taken into account in crop area when the crop-mark is typed out. If the optional parameter is omitted, the crop area coincides with the text area only.

Next four parameters mean padding values for crop-mark corners with respect to the crop area and the last parameter is equal to crop lines length. Its positive value means crop-mark corners looking on the crop area. Otherwise, the corners look outside of the crop area. To prepare crosses, you need to use the crop-mark twice with positive and negative values.

In two-side mode the left and right padding are swapped for every even page.

For example, `\watermark{\cropmark[f]{10mm}{10mm}{10mm}{10mm}{5mm}}` means a crop-mark indented on 10mm in all directions from the crop area containing the text area and the page footer. You can see the result on this page. The crosses on the next page were prepared with the following command:

```
\watermark{\cropmark[f]{10mm}{10mm}{10mm}{10mm}{5mm}}
\cropmark[f]{10mm}{10mm}{10mm}{10mm}{-5mm}
```

2 The Implementation

This package requires the **ncccropbox** package to prepare a crop-mark and the **tocenter** package to calculate crop-area dimensions.

*This file has version number v1.1, last revised 2004/11/29.

```

1 <*package>
2 \RequirePackage{ncccropbox,tocenter}

\cropmark We suppose here that the \cropmark will be used at the beginning of header.
The \NCC@pos command from the toccenter package parses the <fields> parameter
and prepares \NCC@h{<register>}, \NCC@f{<register>}, and \NCC@m{<register>} commands
to adjust values of skip registers. See the toccenter package for more details.

3 \newcommand*\cropmark[6][]{\NCC@pos{#1}%

At the first, we calculate the width of crop-box and the left skip from the beginning
of header. The \@tempswatru means reverse left and right paddings.

4 \@tempswafalse
5 \if@twoside \ifodd\c@page \else \@tempswatru \fi\fi

Set \@tempdima to the left padding and \@tempdimb to the right padding.

6 \if@tempswa
7   \setlength{\@tempdima}{#3}%
8   \setlength{\@tempdimb}{#2}%
9 \else
10  \setlength{\@tempdima}{#2}%
11  \setlength{\@tempdimb}{#3}%
12 \fi

Adjust values of \@tempdima and \@tempdimb with margin widths:

13 \if@twocolumn
14   \NCC@m{\@tempdima} \NCC@m{\@tempdimb}
15 \else
16   \if@tempswa
17     \if@reversemargin \NCC@m{\@tempdimb} \else \NCC@m{\@tempdima} \fi
18 \else
19   \if@reversemargin \NCC@m{\@tempdima} \else \NCC@m{\@tempdimb} \fi
20 \fi
21 \fi

Calculate the left skip in \@tempskipa and the crop-box width in \@tempdima:

22 \@tempskipa -\@tempdima
23 \advance\@tempdima\@tempdimb
24 \advance\@tempdima\textwidth

Now we calculate the height of crop-box in the \@tempdimb register and the bottom
skip in the \@tempskipb register:

25 \@tempdimb\headsep
26 \advance\@tempdimb\textheight
27 \NCC@f{\@tempdimb
28 \addtolength{\@tempdimb}{#5}%
29 \@tempskipb -\@tempdimb
30 \advance\@tempdimb -\headsep
31 \NCC@h{\@tempdimb
32 \addtolength{\@tempdimb}{#4}%

```

All necessary calculations are done. Put the crop-box at the relative position
\\@tempskipa, \\@tempskipb:

```
33  \begingroup
34   \cropelinelength{#6}%
35   \lineskip\z@
36   \\@killglue\\raise\\@tempskipb
37     \\hb@xt@\\z@{\\kern\\@tempskipa
38       \\cropbox[\\@tempdima][\\@tempdimb]{\\hss}\\hss}%
39   \\endgroup
40 }
41 </package>
```